



# EVOPLUS

Efficient, high-technology & eco-friendly  
Circulator pumps with integral Variable  
Speed Drive

# MASTERFLOW

# EVOPLUS CIRCULATORS:

The Evoplus product line consists of a full range of circulators, with a maximum capacity of up to 64 m<sup>3</sup> / h and maximum head up to 18 metres. They are equipped with flanged ports up to DN 100 in single and twin version.

Evoplus circulators are efficient, high-tech, and eco-friendly. Sustainability is the principal driving force behind the make-up and features of the new Evoplus range. The circulators not only comply with the new Ecodesign Directive for 2013, however, they are also ready for the future 2015 European Directive. Thanks to cutting-edge technology, the entire range has an energy efficiency Class A rating, ensuring a reduction in energy wastage and minimising environmental impact.

## APPLICATIONS

- Heating
- Air-Conditioning



# FEATURES



## SMART PRODUCTS

Choosing Evoplus means saving energy thus money and of course respecting the environment. The use of quality components and advanced electronics ensure high performance, low energy consumption and simple product installation and operation. The environmental impact is significantly reduced, thanks to a 70% reduction in energy consumption compared to a traditional circulator.

### ***Evoplus: Intelligence, eco-design and the latest technology at your service***

Leading technology and integrated electronics guarantee constant optimization of the operating system, thus eliminating energy wastage and extending the life cycle of the product. Speed and power are customisable and determined by the specific performance required by the application for which the pump is needed, enabling a more effective and efficient operation.

### ***Simple and Easy to Use***

Evoplus simplifies installation, maintenance and control increasing significant savings in terms of time and cost.

- The clear interface display showing the operating status allows user to select between the different adjustment modes.
- Constant control provided by the remote operation function allows interactive, easy and instant management of the system anytime from anywhere.

## SUSTAINABLE

Sustainability is a strategic choice and a mandatory requirement starting from 2013, thanks to the Ecodesign Directive (Erp). Evoplus circulators with their eco-friendly technology propose a safe change leading towards a sustainable and conscious development.

Erp "Eco-design" 2009/125/CE: includes all "energy-related products" and aims, through several steps, at leading the market towards a wider diffusion of highly efficient and "intelligent" products.

### TECHNICAL INFORMATION

Operating Range	Liquid Temperature Range	Max. Operating Pressure
2 - 75.6 m <sup>3</sup> /h	-10°C to 110°C	16 BAR



**MASTERFLOW**

**ENGINEERED SOLUTIONS  
FOR PUMPS, TANKS, CHILLERS,  
FILTRATION, VALVES & CONTROLS**

**Head Office**

**New South Wales**  
184 Newton Road,  
Wetherill Park 2164  
+61 (2) 9748 2022

**Victoria**

8-10 Parkhurst Drive  
Knoxfield 3180  
+61 (3) 9012 9751

**Queensland**

161 Railway Parade  
Thorneside 4158  
+61 (7) 3103 7055

[masterflow.net.au](http://masterflow.net.au)

[sales@masterflow.net.au](mailto:sales@masterflow.net.au)